



11361 Sunrise Park Drive, Rancho Cordova, Calif. 95742-6587  
 Telephone (916) 638-3344 Fax (916) 636-7453

This model number is controlled by the International Traffic in Arms Regulations, and can only be exported via a U.S. Department of State export license. They may not be transferred, transhipped on a non-continuous voyage, or otherwise be disposed of in any other country, either in their original form or after being incorporated into other end-items, without the prior written approval of the U.S. Department of State.

MODEL NO. MEC 5409 (GR)  
 MEC 5410 (FE)  
 6.5 to 18.0 GHz

TYPICAL OPERATING CONDITIONS			POWER SUPPLY REQUIREMENTS		
ELEMENT	VOLTAGE	CURRENT	VOLTAGE MIN	VOLTAGE MAX	CURRENT MAX
HEATER	-6.3 Vdc	1.6 A	-6.0 Vdc	-6.6 Vdc	2 A
HELIX	W/ RF	GROUND	GROUND	GROUND	15 mA
	W/O RF				
		1 mA			
FE ON	-50 Vdc	0.1 mA	0	-75 Vdc	1 mA
FE OFF	-1300 Vdc	0.1 mA	-1500 Vdc	-1700 Vdc	1 mA
GRID ON	180 Vdc	1 mA	125 Vdc	250 Vdc	10 mA
GRID OFF	-200 Vdc	0.1 mA	-200 Vdc	-500 Vdc	1 mA
CATHODE (Ek)	-10.3 kV	260 mA	-10 kV	-10.5 kV	280 mA
COLLECTOR W/ RF	#1	5.36 kV	45 mA	52% x Ek ± 2%	100 mA
	#2	3.71 kV	208 mA	36% x Ek ± 2%	280 mA

NOTE 1: CATHODE VOLTAGE IS MEASURED WITH RESPECT TO GROUND.  
 NOTE 2: HEATER, COLLECTOR, GRID OR FOCUS ELECTRODE (FE) VOLTAGES ARE MEASURED WITH RESPECT TO CATHODE.

SELECTED PERFORMANCE	TYPICAL	SPECIFIED
INPUT VSWR	2:1	2.5:1
OUTPUT VSWR	2:1	2.25:1
MAXIMUM DUTY	—	CW
FE CAPACITANCE	50 pF	65 pF
GRID CAPACITANCE	37 pF	50 pF
MIN HARMONIC SEPARATION	-6 dBc	-5 dBc *
NOISE POWER DENSITY	-15 dBm/MHz	-10 dBm/MHz
PRIME POWER	1095 W	1400 W
TEMPERATURE RANGE	-40° to 85°C	—

RF PERFORMANCE			
FREQ GHz	TYP SAT POWER OUTPUT (WATTS)	MIN SPEC POWER OUTPUT (WATTS)	TYP GAIN AT SPEC POWER dB
6.5	215	200 *	35
7.0	240	200	40
8.0	250	200	41
9.0	275	200	43
10.0	225	200	45
11.0	275	200	45
12.0	275	200	46
13.0	275	200	46
14.0	275	200	45
15.0	250	200	43
16.0	240	200	41
17.0	230	200	48
18.0	220	200	35

TYPICAL POWER OUTPUT IS SHOWN TO ILLUSTRATE CAPABILITY.

GAIN IS WITH EQUALIZER.

An ISO 9001:2000 Quality System  
 Certified Company

01/06